Most Popular

ANSI color code shown

To order **IEC** color code see pg. A-9

USA

Miniature Connectors
Type SMPW Glass Filled Nylon -29 to 220°C
(-20 to 425°F) Service Temperature
Type HMPW Liquid Crystal Polymer
260°C/500°F Service Temperature


MONOGRAM

HMPW

-29 to 260°C

SMPW

-29 to 220°C




- Color-Coded for ANSI and IEC
- Captive Cover Screws
- Accepts Stranded or Solid Wire up to Size 20 AWG
- Quick Connect Contact Washers
- Internal Wire Divider
- Combination Phillips/Slot Screws
- ✓ Type HMPW Environmentally Friendly Cadmium-Free

Silicone Wire Grommet, SR-SMP **HMPW Series Basic Pair**

NEW!

Crimp Style Brass and Stainless Steel **Bushing**



Available in sizes to fit 0.020 to 0.125" and 1.5 and 3.0 mm diameter probes. See Page G-16

We make running changes when technical advances allow. Check at time of ordering for additional features.

SMPW — Glass-Filled Nylon HMPW — Cadmium Free Liquid **Crystal Polymer** Shown smaller than actual size

Than Actual Size Removable/Reversible

Write-On Window At No Extra Charge


PATENTED

Shown Larger

LIQUID CRYSTAL POLYMER! Covered by U.S and International patents and pending applications

Chisel Point Male Contacts

> Internal Wire Divider




Also Available!

Transmitters and Ferrite Cores for EMI Protection

Model SPRTX Built-in 4 to 20 mA Transmitter \$75. See page N-5.

Model PCLM-FT Cable Clamp with Ferrite Core for EMI Protection, \$2.50 ea. Connector sold separately.

See OMEGA's Complete Selection of Connector Accessories Featured on Pages G-19, G-25 and G-32, and online at omega.com





The write-on connector is a trademark of **OMEGA Engineering. Inc.**

Additional write-on windows available, order WCP-S, \$0.25/pkg of 5.

HMPW Series Basic Pair

Additional silicone wire grommets Order SR-SMP-10, \$0.50/pkg of 10 Order SR-SMP-100, \$5.00/pkg of 100


Quick Connect Contact Washers Additional washers available. Order CW-SMP-20. \$2.00/pkg of 20, or CW-SMP-100, \$8.50/pkg of 100

Removable/Reversible Write-On Window At No Extra Charge

HMPW

PATENTED

Covered by U.S and International patents and pending applications





	Orde	ering E	xample	7			
	Model SMPW - K - M \$1.75						
	SMP	W –	K – I	VI			
	Subminiature Connector	Window Style	\ Calibration	\ Male	\		
2					'		

Discount	Discount Schedule						
1-10	Net						
11-24	10%						
25-49	15%						
50-99	20%						
100-999	25%						
1000 and over	Consult Sales						

ALL MODELS AVAILABLE FOR FAST DELIVERY!

To Order (Specify Model Number) RANGE: -29 to 220°C (-20 to 425°F) RANGE: -29 to 260°C (-20 to 500°F)											
Alloy	Compensating Alloy Used in Connector		Shell	Glass-Filled Nylon	Price Pair Female Male		Male	Liquid Crystal Polymer	Price Pair Female Male		
Code	+	_	Color	Model Number w/ Window	(MF)	(F)	(M)	Model Number w/ Window	(MF)	(F)	(M)
K	CHROMEGA®	ALOMEGA®	Yellow	SMPW-K-(*)	\$4.00	\$2.25	\$1.75	HMPW-K-(*)	\$4.40	\$2.45	\$1.95
T	Copper	Constantan	Blue	SMPW-T-(*)	4.00	2.25	1.75	HMPW-T-(*)	4.40	2.45	1.95
J	Iron	Constantan	Black	SMPW-J-(*)	4.00	2.25	1.75	HMPW-J-(*)	4.40	2.45	1.95
E	CHROMEGA®	Constantan	Purple	SMPW-E-(*)	4.00	2.25	1.75	HMPW-E-(*)	4.40	2.45	1.95
R/S	Copper	RNX/SNX	Green	SMPW-R/S-(*)	4.00	2.25	1.75	HMPW-R/S-(*)	4.40	2.45	1.95
G	GPX	GNX	Red/Grn	SMPW-G-(*)	4.00	2.25	1.75				
C	CPX	CNX	Red	SMPW-C-(*)	4.00	2.25	1.75	HMPW-C-(*)	4.40	2.45	1.95
D	DPX	DNX	Red/Wht	SMPW-D-(*)	4.00	2.25	1.75				
U	Copper	Copper	White	SMPW-U-(*)	4.00	2.25	1.75	HMPW-U-(*)	4.40	2.45	1.95
N	OMEGA-P®	OMEGA-N®	Orange	SMPW-N-(*)	6.00	3.40	2.60	HMPW-N-(*)	6.40	3.60	2.80

^{*}To Order: Specify "MF" for a connector pair, "M" for male connector only, or "F" for female connector only.

Note: Type U (uncompensated) connectors are used with Type B thermocouples (Pt/6%Rh-Pt/30%Rh)

Ordering Examples: SMPW-K-MF, glass-filled nylon, Type K connector pair, \$4.00. SMPW-K-M, glass-filled nylon, Type K male connector, \$1.75. SMPW-K-F, glass-filled nylon, Type K female connector, \$2.25. HMPW-K-MF, liquid crystal polymer, Type K connector pair, \$4.40.

[†]J, K, T, E, R, S and B are ANSI designations. OMEGALLOY® is generically known as Nicrosil-Nisil. ANSI color coded models shown. tt Non-Window models available, please consult Sales for details.

Your One-Stop Source for Process Measurement and Control!

One Omega Drive | Stamford, CT 06907 | 1-888-TC-OMEGA (1-888-826-6342) | info@omega.com

www.omega.com



UNITED STATES

www.omega.com 1-800-TC-OMEGA Stamford, CT.

CANADA

www.omega.ca Laval(Quebec) 1-800-TC-OMEGA

GERMANY

www.omega.de Deckenpfronn, Germany 0800-8266342

UNITED KINGDOM

www.omega.co.uk Manchester, England 0800-488-488

FRANCE

www.omega.fr Guyancourt, France 088-466-342

CZECH REPUBLIC

www.omegaeng.cz Karviná, Czech Republic 596-311-899

BENELUX

www.omega.nl Amstelveen, NL 0800-099-33-44



More than 100,000 Products Available!

Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Glass Bulb Thermometers, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders Relative Humidity Measurement Instruments, RTD Probes, Elements and Assemblies, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples Thermowells and Head and Well Assemblies, Transmitters, Wire

Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Strain Gages, Torque Transducers, Valves

Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters